







Enquiry data sheet **MultiStrip Specials**





Issued (Name / Date): _____



Customer / Prospect / Reference

OSBORN International GmbH
 Ringstraße 10
 35099 Burgwald, Germany
 Tel.: +49 (0) 64 51 / 5 88-149
 Fax: +49 (0) 64 51 / 5 88-208
 eMail: multistrip@osborn.de
 www.strip-brush.com

FormStrip	FormStrip	FormStrip	FormStrip	FormStrip	FormStrip
FIC / Inverted coils	FEC / External coils	FIR / Inverted single ring	FER / External Single ring	FCR / Cup Formed ring	FSF / Special formed strip
					
Qty.					
OD.					mm
ID.					mm
Backing type					Individual drawing or sketch required
Width				mm	
No. of coils	Pitch				mm
Left hand	Right hand				

MultiStrip / MasterStrip (Typ SS)					Alu profiles	
						
Qty.	Type	W	OAT	Length	Type h	Type F
	A	2,5		mm		
	B	4,0		mm		
	C	4,7		mm		
	E	5,1		mm		
	N	5,0		mm		
	K	6,6		mm		
	F	7,8		mm		
	H	8,0		mm		
	L	11,4		mm		
	other			mm		

For drilled profiles an individual sketch is required!

ProfileStrip						
Typ PH			Typ PF			
						
Qty.	Type	F	PW	PH	T	Length
	PFA	10	6	7	mm	mm
	PFB	18	6	7	mm	mm
	PFC	23	6	7	mm	mm
	PFD	33	6	7	mm	mm
	PHA	10	6	7	mm	mm
	PHB	18	6	7	mm	mm
	PHC	23	6	7	mm	mm
	PHD	33	6	7	mm	mm
	PHE	30	10	10	mm	mm
	PHF	40	10	10	mm	mm
	PFE	30	10	10	mm	mm
	PFF	40	10	10	mm	mm

For drilled profiles an individual sketch is required!

Fill material		Backing material				
Material	Nylon	Application	Galvanized (standard)			
	Polypropylene		Stainless steel			
	Steel wire		Sealing			
	Stainless steel wire			Guiding/ Positioning		
	Horsehair mixture			Protecting/ Shielding		
Dia-meter	mm	Cleaning				
	Standard	Transporting				
Crimp	Standard	Antistatic	Dry	Wet	Temperature	°C
	Straight		Liquid/ Environment			
	Crimped					

Description
